


Tuesday (01/10/2012) Briefings

08:30	Intro and MACS Overview
09:40	Break
10:00	MACS/ADRS simulation architecture and integration with ATOS and TMA
11:00	Using MACS to simulate aircraft operations Simulation Manager and Flight Deck Stations
12:00	Lunch
1:00	Basic Air Traffic Control Operations.
1:30	Using MACS to simulate near-term air traffic control operations. Focus ATD-1, Center/TRACON workstations, Scheduling, CMS
2:45	Break
3:00	Using MACS to simulate far-term automated air traffic control operations. <i>Focus on Separation Assurance</i>
3:45	Developing MACS Software
4:30	End of day

Separation Assurance/Function allocation simulation components. MACS pilot and controller stations for en route, ATOS (in preparation)





Using MACS to simulate far-term automated air traffic control operations. Focus on Separation Assurance

Tom Prevot



Overview

- Enroute controller stations in the mid-term
- Automated enroute controller stations in the far-term



Air Traffic Control



AIRSPACE OPERATIONS LAB

En Route Controller Positions




Operator-Mode: Center-Controller



Primary Display: DSR View

DSR: Display System Replacement




Most Relevant Setup Files:

- ATC DST Configuration
- ATC DST Sector Configuration
- DSR Data Tag Rules Setup
- DSR Plan View Setup
- DSR Sector Plan View Setup
- DSR Timeline Setup



En-Route: R-side & D-side DSR





Mid-Term Controller Tools

- 4D trajectory generation for flight plan routing, scheduling, reported FMS trajectories, ADS-B reported state and flight control system targets
- Arrival scheduler and timelines
- Medium-term Conflict detection
- Trial planning and speed advisory functions for metering support
- Automation for automatic transfer of communication and RTA uplinks
- Multi-layered rapid feedback conflict probing
- Weather penetration probe
- Data comm. integration
- Fully automated, semi-automated, manual operations
- AAC Auto-Resolver with Weather avoidance
- Most functions are configured via the ATC DST Configuration



Conflict Probe FDB

Flight Data Block Conflict Information



Font Color Coding for Time-to-Conflict values

- •Red Font: time-to-loss of separation is < 3 minutes</p>
- •Yellow Font: time-to-loss of separation is > 3 minutes < 5 minutes
- •White Font: time-to-loss of separation is > 5 minutes but < 12 minutes



Trial Planning

- Trial Plan Options
 - Single or Multi-Aircraft
 - Typed Commands into DSR CRD
 - FF- selects aircraft for group trial planning
 - TT- opens basic route trial plan
 - TA- opens an altitude trial plan
 - TR- opens a more specified route trial plan
 - Interactive Flight Data Block (FDB)
 - Arrow next to the aircraft call sign- opens basic route trial plan
 - Same arrow (but magenta-colored)- to review a suggested trial plan
 - Altitude line of the FDB- opens an altitude trial plan
 - Conflict number to start a automated trial plan resolution to solve for the predicted traffic conflict
 - Weather number to start a trial plan to solve for the predicted weather penetration
 - Drag and Drop Route Line
 - Lat/Long
 - Waypoint







Air/Ground Data Communication

Key Uplink Capabilities

- Trajectory information [or parameters] and trajectory constraints (route modification uplinks, altitudes, profile speeds, required times of arrival)
- transfer of communication (i.e. frequency changes)
- free text (encode anything in text format)
- responses to aircraft initiated requests

Key Downlink capabilities

- Responses (wilco, reject)
- Free text (encode anything in text format)
- Requested trajectory changes

Broadcast/ downlink capabilities


- Aircraft state and velocities
- Short term intent and flight modes (i.e. flight control system settings)
- FMS trajectory reports
- FMS inputs (e.g. speed profile, weight)

Data Comm: Mixed Equipage **Equipped Data Comm Clearance**



Uplink Clearance to Aircraft (Point and Click)

- 1. Pick on data link portal (filled triangle)
- 2.Drop down box appears next to FDB
- 3. Pick on UC: Clearance to uplink to aircraft



Uplink Clearance via Keyboard

•Type UC [CID] ENTER

Data Comm: Mixed Equipage Un-Equipped Verbal Clearance



Issue TP or CC Clearance to Aircraft (Point and Click)

- 1.Pick on data link portal (underscore symbol)
- 2.Drop down box appears next to FDB
- 3. Voice clearance appears, issue to aircraft Direct PXV, BWG rest of route unchanged
- 4. Pick on QC: Amend in Automation (HOST)







Data Comm FDB Information

AAL207 → 350C 623 482

AAL207→ 350C 623 482

↑ AAL207 → 350C 623 482

Î AAL207 🔁 350C 623 482

status the following data link status symbols are found in the flight data block (left of the call sign):

symbols ♦: eligibility : no eligibility / :TOC in progress ↑: uplink in progress

coordination request (right of callsign)

[•]A filled diamond () indicates that the sector has "eligibility", and can send and receive messages to the aircraft. Data link eligibility usually accompanies track control, but the transfer mechanism is separate.


[•]An unfilled diamond (\lozenge) indicates that the sector does not have "eligibility" (i.e., cannot communicate with this aircraft via CPDLC).

[•]A lightning bolt (**) indicates that a transfer of communication (and transfer of eligibility) is in progress.

[•]An up arrow () indicates that a message has been "uplinked" from the controller to the aircraft. The uplink may be a clearance, frequency, or text message.

[•]A magenta arrow () indicates a coordination request which is a clearance request sent to the CPDLC eligible controller from another ground position or MSP.

Sample Data Comm Transfer of Communication (Air-to-Ground)



TOC View for accepting hand-off frequency change from receiving sector:





Multi Aircraft Control System (MACS)

AIR TRAFFIC CONTROL OPERATIONS FAR-TERM / 2030

30, 40, or 50 aircraft are allowed in Airspace "sectors" at any given time 1 or 2 Air Traffic Controllers per sector possible Video shows 8 controllers handling ~300 aircraft

AIRSPACE OPERATIONS LAB



Air Traffic Control in 2030 ...




AIRSPACE OPERATIONS LAB



Function Allocation used in Study

Automation	Controller
•Detect Separation and weather Conflicts	Supervise the automation
 Resolve trajectory-based conflicts (if within tolerances) 	 Resolve trajectory conflicts flagged by the automation
 Resolve all time-critical traffic conflicts Alert controller to urgent problems Provide trajectory planning assistance Use data comm. to communicate 	 •Monitor and maintain schedule compliance •Implement weather reroutes with automation support •Place aircraft back on trajectory following automated tactical maneuvers








Prototype System


Integrated controller workstation with

- Trajectory planning
- Data communication
- Conflict probing
- Trajectory-based conflict resolution
- Short-term conflict alert and resolution
- Weather avoidance
- Scheduling and time-based metering





Trajectory-based CD&R



Automation status indication integrated in relevant places on the displays

(e.g. resolution, conformance data link status)





Tactical Short-Term CD&R

Vectoring solutions are highlighted in data tag and sent by the automation






Improvements

- Automation
 - Altitude fly-out menu with real-time conflict feedback
 - Free-track trajectory automation
 - Semi-automated weather avoidance
- Human Automation
 Interaction and Procedures







Questions?

Tom Prevot